

ASX RELEASE | 4 June 2025 | ASX: AON

Final Phase 2 Assays – Salanie Gold Project

Apollo Minerals Limited (ASX: AON) ('Apollo Minerals' or 'the Company') provides an update on assay results from drilling activities at the Salanie Gold Project ("Salanie") in Gabon. Recent drilling was following up strong results from the 2024 Phase 1 drilling (the first modern drilling in 70 years), which identified **shallow, high grade gold mineralisation of 5.8m @ 8.2g/t Au from 15.5m** downhole within a broader zone **of 11.7m @ 4.3g/t Au from 9.6m**.

HIGHLIGHTS:

- Assay results for the remaining five diamond holes have now been received for the 14 hole 2025 Phase 2 program.
- The diamond drilling campaign focussed on untested targets at key prospects (A1, A3 and P6) in addition to extensions to the previously reported shallow high-grade mineralisation at A1 of **11.7m @ 4.3g/t Au from 9.6m**.
 - At the A1 prospect, new assay results include **1.0m** @ **0.8g/t** Au from 75m (SLDD016) directly below the historical trench.
- Phase 2 drilling at the P6 Prospect previously intersected mineralisation up to 20g/t Au (1.1m @ 19.9g/t Au from 56m in SLDD013) associated with quartz veining; near historical underground workings.
 - New results at P6 include **3.0m @ 1.0g/t Au** from 74m (SLDD015), **0.6m @ 2.5g/t Au** from 17.5m (SLDD014) and **0.7m @ 1.3g/t Au** from 25m (SLDD015).
 - Only one section has been drilled at P6 and the trend remains untested to the east. Additional work on surface geochemical samples, combined with core structural data is being undertaken to identify trends to the east.
- At A1 South, a 6m wide zone of brecciation, alteration and quartz veining has been intersected in Hole SLDD018 within the interpreted controlling Salanie Fault structure, 170m to the south of A1. The brecciation and veining present strongly supports that this is the continuation of the Salanie Structure.
- Results from the 2025 exploration drilling and mapping are being analysed to define the next phase of work at Salanie.
- The combined results to date demonstrate that the **12km long Salanie greenstone system** maintains strong potential to host gold mineralisation, particularly associated within quartz veining, with further targets still to be tested.

Apollo Minerals' Managing Director, Mr Neil Inwood, commented:

"The Phase 2 drill program has been completed with all assay results now received. The combined results to date reiterate the strong potential for shallow gold mineralisation, particularly with gold associated with quartz veining. The controlling Salanie mineralising structure is open to the north and south in the A1/A2 region and remains largely untested. Results from the 2025 drill program, recent mapping and structural analysis are being reviewed to plan the next phase of activity at Salanie."

For further information contact:

Neil Inwood Managing Director Tel: +61 8 9322 6322 Email: <u>info@apollominerals.com.au</u>



9,930,000N-

9,925,000N

9,920,000N -

Keri

Permit

G4-456

N

Kilometres

655,000E

655,000E

Binda

A1

A3

A2

APOLLO

Salanie Project Regional Prospects

> Salanie Workings



Figure 1: Salanie Prospect displaying regions drilled in the 2025 program.



SALANIE GOLD PROJECT - PHASE 2 DRILLING IN 2025

2025 Phase 2 drilling at Salanie has been completed with all assays now received. The Phase 2 diamond drill program expanded significantly on the previous short 2024 program and targeted highly encouraging results from the A1 (where visible gold in trenching was identified), P6 and the untested A2 and A3 prospects (Figure 4). The A1, A3 and P6 prospects were host to historical high-grade small-scale open-pit and underground mining in the mid 1950's. Access constraints meant that the greenfield Mikouma and Binda prospects were not tested in the current program.

Prior to the Company's field work, there had been no exploration conducted on the region for 70 years. A total of 14 diamond holes for 1,695 metres were drilled from February to April. Significant results are summarised in Appendix 1.

A1 Prospect Results

At the A1 prospect, drilling followed up on near-surface gold mineralisation, which was encountered in the late 2024 field program. Trenching at A1 also exhibited localised visible gold (Figure 3) at surface. The 2024 diamond drilling intersected shallow gold mineralisation of **11.7m @ 4.3g/t Au from 9.6m** downhole including **5.8m @ 8.2g/t Au from 15.5m;** associated with localised visible gold in late-stage quartz veinlets (Figures 2 and 5).

Significant results from the follow up Phase 2 drilling in 2025 included **3.8m @ 1.3g/t Au from 17.5m** in hole SLDD006 and the newly reported **1.0m @ 0.8g/t Au** from 75m in hole SLDD016.

Based upon an analysis of structural data from the drilling and mapping of additional exposure in the A1 area, it is believed that the A1 main veining has a strong north-south control and remains open to the north but is also varying in intensity along strike and at depth. The cross-cutting quartz veinlets with noted visible gold (Figures 2 and 3) are interpreted to be later-stage, but related to, the main north-south trending main Salanie vein system.



Figure 2: Examples of visible gold identified in SLDD004 – at 19.04m (associated with chalcopyrite (Cpy) and galena (Gn)). (Refer announcement 21 November 2024.)



Figure 3: Insitu gold in veining at A1 drill pad (LHS) and artisanal gold grains from Binda artisanal working (RHS) (refer Announcement 26 August 2024)



The Company cautions that visual estimates of sulphides or mineral abundance should never be considered a proxy or substitute for laboratory analysis. Laboratory analysis would be required to determine the widths and grades of sulphides, visible gold, or suspected mineralised intervals reported herein. Visual information also potentially provides no information regarding impurities or deleterious physical properties relevant to valuations

A1 South Prospect Results

In the A1 South region, hole SLDD018 was drilled to test the Salanie fault position south of the A1 workings and known mineralisation. Importantly, SLDD018 intersected a 6m wide zone of brecciation, alteration and quartz veining (from 38m) that is approximately 170m south of A1.

Although no significant assays were received from the hole, it is interpreted that the brecciation, alteration and veining is related to the Salanie Fault that is thought to control mineralisation along the A1 to A3 trend (Figures 4 and 5).



Figure 4: Drilling in the A1 to A3 areas.



9,921,800N

Zone of brecciation &

alteration

651,400E

3.8m @ 1.0 g/t Au

1.4m @ 15.7 g/t Au

Salanie Fault Trend

SLDD018

651,400E

10.3m @ 3.4 g/t Au

1m @ 0.8 g/t Au

SLDD007

11.7m @ 4.3 g/t Au 5.8m @ 8.2 g/t Au

3.0m @ 5.1 g/t Au

SLDDOQ6

Q SLDD016

O,

100

UTM

metres WGS84 Zone 32s

Figure 5: A1 Drilling Region.

SLDD008

See. **APOLLO**

Salanie Project A1 Prospect Drilling



Significant intersections from the current announcement at P6 include 3.0m @ 1.0g/t Au from 74m (SLDD015), 0.6m @ 2.5g/t Au from 17.5m (SLDD014) and 0.7m @ 1.3g/t Au from 25m (SLDD015). The mineralisation is associated with quartz veinlets and appears to be associated with the felsic intrusive contacts.

Only one section has been drilled at the P6 Prospect and the trend remains untested to the east. Additional work on surface geochemical samples, combined with core structural data is being undertaken to identify trends to the east.







Figure 6: Long Section of the P6 drilling.



Figure 7: Location of P6 drilling.



Salanie Gold Project Overview

The Salanie Gold Project is located 16km from the major town of Lambarene, less than 2km from the sealed N1 highway, and lies within the Company's 100% owned Keri Permit (G4-456) approximately 3.5 hours by road from the capital city of Libreville. Historical mining at the Project in the mid-1950's produced a reported +20,000 ounces of gold at 12g/t Au from mining of outcropping quartz veins with the remainder from alluvial/eluvial workings.

Regional and Local Geology

The Project is centred on an underexplored greenstone belt comprised of Archaean migmatites, amphibolite and granitic porphyry intrusions. The area is within the Lambarene Horst, which is an area of metamorphosed Archaean rocks flanked by Cretaceous sediments of the Cotier Basin to the west. The main structural trends are parallel to the regional Ikoy-Ikobe Shear in a NNW-SSE direction. Mapping undertaken to date has identified sheared felsic gneiss, granitic units, amphibolites, minor ultramafic units and generally confirmed historical mapping details.

Mineralisation Styles

Primary gold mineralisation is hosted with quartz-sulphide veins within the Archaean migmatites. Sulphides identified within the quartz dominant veining include chalcopyrite, galena, pyrite and marcasite. Historically, quartz veins are described to range from one to three metres wide with a general orientation of NNW-SSE trend dipping 30-50 degrees to the NE. The areas of previous gold mineralisation identified and mined are along the Salanie Fault (A1, A3) and P6 areas.

Alluvial gold within streams is noted for an approximately 9km trend through the Project area with the gold interpreted to be sourced from primary quartz veining from local catchments. Additionally localised gold mineralisation within pisolite-rich weathered material has been noted historically.

Recent surface trench mapping identified an interpreted shear system at the A1 prospect with insitu mineralisation of 10.3m @ 3.4g/t in trenching as well as a separate interval of 1.4m @ 15.7g/t Au. Surface spoil samples 80m up-hill of the trenching have also shown results of up to 429g/t Au.



Figure 8: Salanie Gold Project.

COMPETENT PERSONS STATEMENT

The information in this announcement that relates to exploration results is based on information reviewed by Mr Alex Aitken, a Competent Person who is a Member of the Australian Institute of Geoscientists. Mr Aitken is the Technical Manager for Apollo Minerals and a holder of incentive options in Apollo Minerals. Mr Aitken has sufficient experience that is relevant to the styles of mineralisation and types of deposit under consideration, and to the activity being undertaken, to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves" (JORC Code). Mr Aitken consents to the inclusion in the announcement of the matters based on his information in the form and context in which it appears.

The information in this announcement that relates to previous exploration results are extracted from the Company's ASX announcements including 19 July 2023, 29 August 2023, 13 September 2023, 15 November 2023, 19 December 2023, 13 March 2024, 15 April 2024, 30 July 2024, 26 August 2024, 21 November 2024, 11 December 2024 and 5 May 2025 and are available to view on the Company's website at www.apollominerals.com. The Company confirms that a) it is not aware of any new information or data that materially affects the information included in the ASX announcements; b) all material assumptions included in the ASX announcements continue to apply and have not materially changed; and c) the form and context in which the relevant Competent Persons' findings are presented in this report have not been materially changed from the ASX announcements.

FORWARD LOOKING STATEMENTS

Statements regarding plans with respect to Apollo's project are forward-looking statements. There can be no assurance that the Company's plans for development of its projects will proceed as currently expected. These forward-looking statements are based on the Company's expectations and beliefs concerning future events. Forward looking statements are necessarily subject to risks, uncertainties and other factors, many of which are outside the control of the Company, which could cause actual results to differ materially from such statements. The Company makes no undertaking to subsequently update or revise the forward-looking statements made in this announcement, to reflect the circumstances or events after the date of that announcement.

This announcement has been authorised for release by the Company's Managing Director, Mr Neil Inwood.



Appendix 1: Drill Hole Information – Saline Gold Project - Gabon

Table 1: Drill Results from the complete 2025 Phase 2 drilling program (results in the current announcement are highlighted in grey).

Prospect	Hole ID	Fasting	Northing	Azimuth	Din	EOH	From	Length	Au (ppm)	Au (ppm)
Trospect		Lasting	Northing	Azimati		depth	(m)	(m)	Photon	Fire Assay
A1	SLDD006	653328	9921796	90	-60	60.7	17.5	3.8	0.95	1.32
						inc	19	0.9	1.58	4.41
							20.51	0.5	3.04	1.49
A1	SLDD007	653305	9921808	135	-60	99.8	26.9	0.61	0.08	0.13
							72	1	0.22	0.003
A1	SLDD008	653274	9921800	135	-50	79.9			Ν	ISA
A1	SLDD016	653313	9921766	90	-50	123	74.98	1.02	0.82	
A1 South	SLDD017	653413	9921591	50	-60	33.2		Hole was	abandoned	, redrilled by SLDD018
A1 South	SLDD018	653412	9921590	45	-50	147			N	ISA
A3	SLDD009	653718	9921303	240	-50	102.05			N	ISA
A3	SLDD010	653764	9921310	240	-50	149.9			N	ISA
A3	SLDD011	653807	9921269	240	-50	156	74.51	0.37	0.69	0.02
P6	SLDD012	651345	9919933	270	-60	140.9			Ν	ISA
P6	SLDD013	651345	9919994	270	-70	163.5	38.7	1	1.23	3.58
							56	1.05	0.93	19.94
							116.3	1	0.8	0.14
P6	SLDD014	651299	9920069	270	-70	137.8	17.47	0.6	2.47	1.71
							72.15	2.23	0.35	
P6	SLDD015	651337	9919965	270	-70	145.9	25	0.66	1.32	1.14
							74	3	1.0	1.0
							97.45	0.65	0.23	
							102.22	0.48	0.68	0.92
P6	SLDD019	651346	9919929	220	-80	156	98.2	1.85	0.35	

Note: Low grade intercepts are shown using a nominal 0.4ppm Au cutoff; high-grade intercepts are shown uncut. NSA: No significant assays. Salanie coordinates are in UTM WGS84.

Prospect	Hole ID	Easting	Northing	Azimuth	Dip	EOH depth	From (m)	Length (m)	Au (ppm) Fire Assay
P6	SLDD001	651335	9919969	290	-60	53.77	7.36	0.59	0.01
P6	SLDD002	651329	9920029	270	-70	89.14	41.63	1.12	0.28
							61.2	5.3	0.27
						inc	61.2	0.45	1.16
						inc	65.45	1	0.75
A1	SLDD003	653316	9921741	100	-50	34.9	13.14	0.15	0.35
A1	SLDD004	653338	9921791	135	-60	59.48	9.62	11.67	4.31
						Inc	15.45	5.84	8.24
						Inc	18.93	0.36	124.87
A1	SLDD005	653322	9921762	135	-60	91.2		NSA	



Appendix 2

JORC Code, 2012 Edition – Table 1 Report for Salanie Gold Project, Gabon

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.	Diamond Core was cut in half to produce a ½ core (HQ & NQ) or ¼ core (PQ) samples using a core saw - DDH. A combination of PQ, HQ and NQ size core has been cut. All sampling was either supervised by, or undertaken by, qualified geologists. ½ and ¼ core sample sizes ranged from 0.3 to 1.1m in length. Drill hole locations were surveyed using Garmin 65S GPS equipment achieving sub metre accuracy in horizontal and vertical position.
		QAQC. See further details below.
	Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.	Core samples are selected based on geological criteria (presence of veining and sulphide mineralisation).
Drilling techniques	Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	PQ-HQ-NQ-sized core drilling has been completed. Drill holes are angled ranging from -50 to -80 degrees.
Drill sample recovery	Method of recording and assessing core and chip sample recoveries and results assessed.	Drill hole recoveries were recorded during logging by measuring the length of core recovered per 1m interval with core recoveries averaging 95% overall
	Measures taken to maximise sample recovery and ensure representative nature of the samples.	Drilling is carried out orthogonal to the interpreted mineralised trend to get representative samples of the mineralisation.
	Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	No relationship between recovery and grade has been identified to date in the data review stage.
Logging	Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	All drill core was logged onsite by geologists to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.
	Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.	Logging is qualitative and records lithology, grain size, texture, weathering, structure, alteration, veining, and sulphides. Core is digitally photographed.
	The total length and percentage of the relevant intersections logged.	All holes are logged in full.
Sub- sampling techniques	If core, whether cut or sawn and whether quarter, half or all core taken.	Core is cut using a diamond saw and $\frac{1}{2}$ & $\frac{1}{4}$ core is submitted for assaying.



Criteria	JORC Code explanation	Commentary
and sample preparatio n	If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.	N/A
	For all sample types, the nature, quality and appropriateness of the sample preparation technique.	Core sample preparation at Intertek Laboratory (Intertek – Libreville, Gabon) consists of crushing entire cut core samples (up to 3kg) to 80% passing -10 mesh, splitting 300 grams, and pulverizing to 95% passing -150 mesh. The ICPMS analysis uses a 150g pulp assayed at Intertek, Perth.
		A sub-sample of the -2mm crushed sample was taken in the Intertek Gabon and shipped to Ghana for analysis by Photon Assay. A 500-600g 'crush-split' sample was utilised for Photon Assay in Intertek Ghana.
	Quality control procedures adopted for all sub- sampling stages to maximise representivity of	All cut core samples are selected from the same side to remove sample bias.
	samples.	Internal QA/QC procedures involve the use of standards, blanks which are inserted into sample batches at a frequency of approximately 1:30.
	Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.	Core is marked for sampling along a marked sample/cut line and a consistent half of core is sampled along the drill hole. No field duplicates were completed for this program.
	Whether sample sizes are appropriate to the grain size of the material being sampled.	Sample sizes are considered appropriate to give an indication of mineralisation.
Quality of assay data and laboratory	The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.	Core samples were assayed at Intertek Perth where the entire sample was crushed, a 300g split was pulverised and a charge digested by ore grade multi-acid digest and analysed by ICP-MS or ICP-OES.
tests		Intertek Ghana undertook Photon Assays, where a 500- 600g, -2mm sample was analysed for gold. The Photon Assay technique was developed by CSIRO and Chrysos Corporation and is a fast, chemical free non-destructive, alternative using high-energy X-rays to traditional fire assay and uses a larger samples size (500g vs 25g fire assay). The technique is accredited by NATA.
	For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.	Olympus Vanta M series handheld XRF with 30 sec reading times. pXRF unit is calibrated using internal calibration prior to analysing each drill hole. Unit is tested against commercial pulp standards regularly during the field season.
	Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.	Certified reference material (CRM) samples sourced from Geostats and were inserted every 30 samples and Blank samples. Specific gold standards used were G315-4, G317-1 and G914-3 selected by the AON geologist.
Verificatio n of sampling and assaying	The verification of significant intersections by either independent or alternative company personnel.	Core samples are analysed by a commercial laboratory, and these results will be reported when received and processed. Significant intercepts are validated back to original laboratory received sheets; and check against geology. Hand Held pXRF analysis is also undertaken on core and used as a guide to assess early stage understanding of mineralisation.
	The use of twinned holes.	N/A
	Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.	All drill hole logging is completed on digital logging templates with built-in validation. Logging spreadsheets are uploaded and validated in a central MS Access database. All original logging spreadsheets are also kept in archive



	Crit <u>eria</u>	JORC Cod
		Discuss any
	Location of data points	Accuracy ar holes (colla mine workin Resource e
		Specification
		Quality and
	Data spacing and distributio n	Data spacin
		Whether th sufficient to grade com Resource procedure(s
		Whether sa
(D)	Orientatio n of data in relation to geological structure	Whether th unbiased sa extent to w deposit type
		If the relation and the orien considered to should be as
	Sample security	The measur
	Audits or reviews	The results techniques a
	Section (2 Reporting
	Criteria	JORC Co

Criteria	JORC Code explanation	Commentary
	Discuss any adjustment to assay data.	N/A.
ocation of data points	Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.	GPS coordinates of drill hole locations were captured using a Garmin GPS in UTM WGS84 Easting/Northing coordinates with metric accuracy in horizontal and vertical position.
	Specification of the grid system used.	Sample locations are provided as UTM co-ordinates within Zone 32, southern hemisphere using WGS 84 datum.
	Quality and adequacy of topographic control.	Topographic control is based on topographic contours sourced from SRTM/ALOS data.
Data spacing and listributio n	Data spacing for reporting of Exploration Results.	Drill hole spacing for the 2025 drill program is variable as drilling to date is first pass drilling of new exploration targets.
	Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.	Further work is required at the Project to test for extension of mineralisation potential. The current data set is considered potentially appropriate for use in a future Mineral Resource providing further drilling is completed.
	Whether sample compositing has been applied.	No compositing of samples in the field was undertaken.
Drientatio n of data n relation o geological structure	Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.	It is considered the orientation of the bulk of the drilling and sampling suitably captures the dominant "structure" of the style of mineralisation at the Project. Indications of some structure in the drill core will require follow up drilling to assist in structural interpretation.
	If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.	This is not currently considered material.
Sample security	The measures taken to ensure sample security.	All core sample intervals are labelled in the core. Cut core samples are collected in bags labelled with the sample number. Samples are delivered to the Intertek, Libreville sample preparation facility directly by AON personnel or transport contractors. The samples were then transported to the Intertek Genalysis Laboratory in Perth and Ghana for geochemical analysis.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	All QAQC data is reviewed to ensure quality of assays; batches containing standards that report greater than 2 standard deviations from expected values are re- assayed.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	The Project consists of two Prospecting License (Ndolou - G4-569 & Keri - G4-456), covering approximately 2,363.5km ² located in Ngounié Province, western Gabon. Apollo Minerals owns 100% of the Kroussou Project through its 100% wholly owned Gabonese subsidiary, Select Explorations Gabon SA.
		The Company notes that under the 2019 Mining Code, the Gabonese State retains the rights for a 10% free carry for the mining of most commodities, with rights to acquire an additional 25% at commercial terms. The Company understands that a recent decree by the Ministry of Mines has altered these rights for 'sovereign minerals' (gold,



Criteria	JORC Code explanation	Commentary
		uranium, diamonds, gems and rare earths) to a systematic right of participation of 35%, free of any charge and non- dilutable, in the capital of companies (i.e local subsidiaries) operating a large-scale mine. Significant uncertainty exists about the changes brought upon by the decree. The Company is seeking legal advice and clarification from both the Ministry and Gabonese government, as to the decree's precedence to the current Mining Code and to its implementation for existing licenses.
		Havilah Consolidated Resources (HCR) holds a 0.75% NSR in Prospecting License (G4-569). This royalty may be bought back from HCR for US\$250,000.
		The Kroussou Prospecting License was granted in July 2015 and renewed in July 2018 and again in November 2021 & 2025 for an additional three years to March 2028.
		The Keri Prospecting licence was granted in August 2022 for a period of three years.
		No historical cultural sites, wilderness or national parks are known or located within the Prospecting Licenses.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	Tenure in the form of a Prospecting License (<i>Permis de Recherche</i>) which has been granted and is considered secure. In accordance with the Gabonese Mining Code, the Prospecting Licenses may be extended for a further three years.
		Apollo Minerals are not aware of any impediments relating to the license or area.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	Exploration in the Salanie area has been conducted by several companies since 1939 through to ~1990. Initial exploration was undertaken by Ngounie Mining Company from 1939 to 1955. The French Bureau de Recherches Géologiques et Minières (BRGM) conducted minor prospecting activities in 1974.
		Alluvial mining operations were undertaken from ~1947 to 1955, a significant amount of gold was extracted via alluvial methods with approximately 450kg of gold reported to be produced. Numerous trenches and wells are reported in the historical documents. The Gabonese Department of Mines produced the geological map at 1:1,000,000 and the 1:200,000 Lambarene in 2009 that covers the Salanie area.
Geology	Deposit type, geological setting and style of mineralisation.	Project area is comprised of Archean migmatites, amphibolite and granitic porphyry intrusions, there has been several major faults interpreted in the areas. Mineralisation appears to be hosted in quartz-sulphide veins parallel to the main foliation of NW-SE trend. Historical reports have noted several auriferous quartz veins in the area that appear to be associated with interpreted faults on the 1:200,000 map sheet.
		Apollo Minerals is exploring for shear hosted gold mineralisation hosted within the Archean basement units, that provided the Salanie alluvial operations.
		Additionally, the western portion of the Keri Permit is still prospective for base metal mineralisation due to the same lithostratigraphic sequence extends north along the basin/ basement contact from the southern Kroussou Project.
		The deposit style reported in BRGM historical files for base metal mineralisation is Mississippi Valley Type (MVT) sedimentary mineralisation of Pb-Zn-(Ag) where mineralisation is similar to the Laisville (Sweden) style with deposition within siliciclastic horizons in a reducing environment.
		On a regional scale, the Ph-Zn mineral concentrations are



Criteria	JORC Code explanation	Commentary
		distributed at the edge of the continental shelf which was being eroded during Lower Cretaceous time. Mineralisation is located within the Gamba Formation part of the N'Zeme Asso Series and was deposited during the Cretaceous as part of the Cocobeach Complex deposited during formation of the Cotier Basin.Mineralisation is hosted by conglomerates, sandstones and siltstones deposited in laguno-deltaic reducing conditions at the boundary of the Cotier Basin onlapping continental basement rocks. Large scale regional structures are believed to have influenced mineralisation deposition.
Drill hole Information	A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: • easting and northing of the drill hole collar • elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar • dip and azimuth of the hole • down hole length and interception depth • hole length.	All new drill hole details are provided in Appendix 1.
	If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	N/A
Data aggregation methods	In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.	No top cuts have been applied to the reporting of the assay results. Overall sample recovery is predominantly > 70%; intervals with no sample recovery have not been diluted in the compositing process. Composite intervals with significant core loss have not been reported as drill core assays.
	Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.	Higher grade intervals are included in the reported grade intervals; and have also been split out on a case-by-case basis where relevant.
	The assumptions used for any reporting of metal equivalent values should be clearly stated.	No metal equivalent values are used
Relationship between mineralisati on widths and intercept lengths	These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.	Down-hole lengths are reported.
	If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').	The exploration drilling was conducted so that results would be close to orthogonal to the mineralisation as understood at the time. As such, the intercepts are interpreted to be close to true thickness of the mineralisation.
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	Appropriate diagrams, including geological plans, are included in the main body of this release.
Balanced reporting	Where comprehensive reporting of all Exploration Results is not practicable,	The exploration results should be considered indicative of mineralisation styles in the region. Exploration results



Criteria	JORC Code explanation	Commentary
	representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.	stated indicated highlights of the drilling and are not meant to represent prospect scale mineralisation.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	All meaningful and material information is reported.
Further work	The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).	Additional drilling along strike of current prospects and follow up of other surface mineralised prospects. Additional surface exploration programs comprising soil surveying, geological mapping, rock chip sampling to further assess identified prospects and to generate new targets within the broader project area.
	Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.	These diagrams are included in the main body of this release.