

FURTHER MINERALISED EXTENSIONS AND DEPTH POTENTIAL AT KOPSA NORTH

**Further mineralised extensions drilled in the northern zone at Kopsa;
geophysical interpretation of the electromagnetic (EM) anomalies around the
new northern high-grade zone suggest potential at depth.**

HIGHLIGHTS

- Assays received from three further holes drilled along the northern contact at Kopsa all confirm mineralised extensions along strike and at depth, and beyond the current resource boundary.
 - One newly collared hole and two extensions to previously drilled holes.
- Significant intersections included¹:
 - **55m @ 0.47g/t Au, 0.18% Cu (0.67g/t AuEq²)** and 2g/t Ag from 291m (NRKOP25005-ext) incl **4.5m @ 2.50g/t Au, 0.19% Cu (2.70g/t AuEq)** and 5g/t Ag from 340m;
 - and **15m @ 0.48g/t Au, 0.12% Cu (0.61g/t AuEq)** and 3g/t Ag from 368m.
 - **4.7m @ 0.82g/t Au, 0.17% Cu (1.00g/t AuEq)** and 4g/t Ag from 212m (NGKOP22013-ext).
 - **3.2m @ 1.21g/t Au, 0.40% Cu (1.64g/t AuEq)** and 8g/t Ag from 101m (NRKOP26030);
 - and **16m @ 0.41g/t Au, 0.33% Cu (0.77g/t AuEq)** and 7g/t Ag from 132m.
- All holes were drilled into gaps in the current resource, reporting extensions to the known mineralised lodes between 30-100m beyond the current resource block model.
- Interpretation of the EM survey results from the zone around the previously reported high-grade intersections in the north of Kopsa³ indicates potential for significant depth continuity, as shown in Figure 4 in this Announcement.
- Three step-out holes in the Southwest of the **815koz AuEq Kopsa deposit**⁴ were drilled as the final part of the Spring 2026 drill program, with assays expected shortly.
- Results from the Kopsa metallurgical test program are expected during Q3 2026. It is intended to compile all new information into an updated resource statement for Kopsa once these results are obtained. Drilling is scheduled to re-commence in two to three week.
- The Company remains well-funded with over A\$10M at bank as at end March 2026.

Nordic Resources Limited (ASX:**NNL**; or **the Company**) reports the results from next three holes, totalling 559m of diamond core, from its Spring 2026 drill program at the Kopsa gold-copper project located in the Middle Ostrobothnia Gold Belt (MOBG) of central Finland. These holes are located in the northern zone at Kopsa.

¹ Full table of drillholes and significant intersections is provided in Appendix 1.

² AuEq formula uses US\$3,000/oz gold price and US\$10,000/t copper price. A recovery factor of 80% is applied for Au and 85% for Cu based on the 2012 Kopsa NI43-101 metallurgical studies and the 2013 Kopsa PEA by NNL's consultant Mr Chris Martin. Resultant formula is AuEq (g/t) = Au (g/t) + 1.102*Cu (%). In the Company's opinion, the metals included in the equivalent calculation (Au,Cu) have reasonable potential to be both recovered and sold.

³ Refer NNL ASX Announcement "Kopsa Drilling Hits Stunning High Grade Gold in Northern Zone", 15 June 2026.

⁴ Including Measured, Indicated and Inferred resources. 69% of the AuEq ounces at Kopsa are in the Measured and Indicated resource categories. Refer to Table 1 later in this Announcement.



Drilling Results

A plan map showing the Company's 2025 and 2026 reported drill hole locations at Kopsa is provided in Figure 1, as a summary of the Company's Kopsa drilling thus far. The 2025 and 2026 drilling has not yet been incorporated into an updated resource for Kopsa. The three new 2026 drill holes with results reported in this announcement are labelled in **bold**. This map also includes the locations of the historical drill hole collars at Kopsa. The gold/copper mineralisation intersected is shown in AuEq terms along the drill traces.




Figure 1: Plan map of Kopsa showing the drill hole collars and traces from the 2026 drill holes reported in this Announcement, the Company's 2025-26 drill collar locations reported thus far, the current MRE outline projected to surface, and historical drill collar locations. See Figure 2 for the marked cross section. See Appendix 1 for full drill hole details. Coordinates presented in ETRS-TM35FIN system (EPSG:3067).

All three holes reported in this Announcement tested the northern contact of the host tonalite intrusive unit and were drilled into gaps in the current resource block model. All holes reported good continuity with previously drilled mineralisation and have extended the mineralised zone between 30-100m beyond the existing resource boundary.

The most significant mineralised extensions were reported in the hole NRKOP25005 extension which intersected a wide mineralised lode commencing over 100m beyond the nearest part of the existing block model, as shown in section A in Figure 2 below.




Figure 2: Kopsa cross section showing extension to hole NRKOP25005. The most recent MRE outline and the interpreted extent of the tonalite intrusion are also shown in this 30m thick section view. See Appendix 1 for the drill hole details. Coordinates presented in ETRS-TM35FIN system (EPSG:3067).

As seen in section A, NRKOP25005-ext has confirmed two significant zones of mineralisation at and above the northern contact. This recurring mineralisation at the northern contact was entirely unknown prior to NNL's 2025 drill program. The main significant intersections from this hole were⁵:

- **2.0m @ 1.61g/t Au, 0.08% Cu (1.69g/t AuEq)** and 2g/t Ag from 204.6m;
- and **54.6m @ 0.47g/t Au, 0.18% Cu (0.67g/t AuEq⁶)** and 2g/t Ag from 291.3m
incl **4.5m @ 2.50g/t Au, 0.19% Cu (2.70g/t AuEq)** and 5g/t Ag from 340m;
- and **15m @ 0.48g/t Au, 0.12% Cu (0.61g/t AuEq)** and 3g/t Ag from 368.3m.

The second extension hole reported here, NGKOP22013-ext, was a short extension hole to pierce the northern contact in the NW part of Kopsa and confirmed some continuity of mineralisation at the contact in this area with an intersection of:

- **4.70m @ 0.82g/t Au, 0.17% Cu (1.00g/t AuEq)** and 4g/t Ag from 211.9m.

Hole NRKOP26030 was drilled nearer to the western end of the northern contact, an area with little prior drilling. This hole confirmed continuity with existing shallow mineralised lodes, extending this more copper-rich mineralisation at depth by 30m. The main intersections lying outside the current block model were:

- **3.15m @ 1.21g/t Au, 0.40% Cu (1.64g/t AuEq)** and 8g/t Ag from 101.2m;
- and **15.8m @ 0.41g/t Au, 0.33% Cu (0.77g/t AuEq)** and 7g/t Ag from 132.4m.

⁵ Intersections are quoted as downhole widths. True thicknesses are estimated to be 70-80% of downhole width. Full table of drillholes and significant intersections is provided in Appendix 1.

⁶ AuEq formula uses US\$3,000/oz gold price and US\$10,000/t copper price. A recovery factor of 80% is applied for Au and 85% for Cu based on the 2012 Kopsa NI43-101 metallurgical studies and the 2013 Kopsa PEA by NNL's consultant Mr Chris Martin. Resultant formula is AuEq (g/t) = Au (g/t) + 1.102*Cu (%). In the Company's opinion, the metals included in the equivalent calculation (Au,Cu) have reasonable potential to be both recovered and sold.

The holes reported in this Announcement were positioned and drilled prior to confirmation of the northern high-grade zone recently reported by the Company⁷ and not designed to test it. However, the Company has commenced detailed analysis of the historical geophysical surveys from this area to prepare for further drilling planned in the second half of the year. As a reminder, this high-grade zone is located at and around section B highlighted in the plan map below (Figure 3).




Figure 3: Plan map of Kopsa marking the location of the main high-grade section B, the Company's 2025-26 drill collar locations reported thus far, the current MRE outline projected to surface, and historical drill collar locations. See Figure 4 for the marked cross section. See earlier ASX Announcement⁷ for the full drill hole details. Coordinates presented in ETRS-TM35FIN system (EPSG:3067).

Given that it was EM survey results that initially encouraged the Company to drill test the northern contact at Kopsa, the Company undertook some further analysis on these EM plates.

The cross-section B is plotted alongside the previously interpreted fixed loop EM (FLEM) and borehole EM (BHEM) plates⁸ in Figure 4. The Company makes the following observations:

- The modelled EM plates correctly predicted the absence of significant high-grade mineralisation in the shallower part of the contact, as tested by NRKOP25016.
- The holes with the better zones of higher-grade mineralisation, coinciding with visual evidence of more intense (stockwork-style) veining are intersecting with the upper parts of the modelled FLEM but did not test deep enough to intersect the modelled BHEM plates.
- All modelled EM plates indicate a stronger EM response below hole NRKOP26024 than above it, suggesting the potential for continuity at depth in this part of the Kopsa deposit.

The Company cautions that while geophysical results can reveal genuine targets, it is only one targeting vector, and there may be other explanations for enhanced EM responses. In addition, geophysical data interpretation necessarily involves certain modelling assumptions which can cause inaccuracy.

The Company intends to conduct downhole EM surveys in holes NRKOP25012B and NRKOP26024 in the near future in order to confirm the style of mineralisation that may be causing an EM response

⁷ Refer NNL ASX Announcement "Kopsa Drilling Hits Stunning High Grade Gold in Northern Zone", 15 June 2026.

⁸ Refer NNL ASX Announcement "First Drill Results Confirm High Grade Gold Near Surface at Kopsa", 10 November 2025, for geophysical survey details.

and better define any genuine EM responses in this zone. This will assist in drill targeting for the next drill program at Kopsa, due to commence in three weeks' time.




Figure 4: Kopsa cross section B showing holes NRKOP25016, NRKOP25012B and NRKOP26024. The most recent MRE outline, the interpreted extent of the tonalite intrusion and the previously modelled EM plates are also shown in this 30m thick section view. The EM plates are shown in their entirety to 600m vertical depth and not sliced to 30m thickness. See earlier ASX Announcement⁷ for the full drill hole details. Coordinates presented in ETRS-TM35FIN system (EPSG:3067).

Management Comment

Commenting on the results, NNL's Managing Director, Robert Wrixon, said: "Kopsa drilling continues to reveal additional mineralisation in the northern zone and along the northern contact of the host intrusion. The EM results provide an indication of potential continuity of the higher-grade zone at depth and this will be tested later this year.

These three northern holes are the third batch of results from the spring 2026 drill program at Kopsa. A final three holes were drilled at Kopsa to test further strike and depth extensions in the southwestern zone, before the drilling concluded at the end of May. The Company looks forward to reporting these assay results shortly and compiling them, together with the 2025 drill results, into an updated resource for Kopsa due later this year. Drilling is to re-commence in 2-3 weeks".

Mineral Resource Estimate

The Company's Kopsa deposit in central Finland currently hosts a near-surface JORC (2012) compliant resource (comprising Measured, Indicated and Inferred categories) of 23.2Mt @ 1.09g/t AuEq for 814,800oz AuEq. The overall resource inventory across all the three MOGB gold projects currently stands at **34.3Mt @ 1.11g/t AuEq for 1.23Mt AuEq, consisting 1.04Moz of contained gold and 38kt of contained copper** across all resource categories, as per Table 1 below. 66% of this resource inventory is currently in the Measured and Indicated categories.

NNL confirms all material assumptions and technical parameters underpinning the Resource Estimates continue to apply and have not materially changed as per Listing Rule 5.23.2.

MOGB Gold Project Resources⁹

Mineral Resources	Tonnes (Mt)	Au (g/t)	Cu (%)	AuEq (g/t)	Au (Moz)	Cu (kt)	AuEq (Moz)
Kopsa							
Measured Resources	7.44	0.95	0.16	1.18	0.23	12	0.28
Indicated Resources	8.96	0.73	0.16	0.97	0.21	14	0.28
Inferred Resources	6.75	0.89	0.19	1.17	0.19	13	0.25
Kopsa Total	23.2	0.85	0.17	1.09	0.63	38	0.81
Angesneva							
Indicated Resources	3.85	1.19	-	1.19	0.15	-	0.15
Angesneva Total	3.85	1.19	-	1.19	0.15	-	0.15
Hirsikangas							
Indicated Resources	2.69	1.17	-	1.17	0.10	-	0.10
Inferred Resources	4.60	1.10	-	1.10	0.16	-	0.16
Hirsikangas Total	7.29	1.13	-	1.13	0.26	-	0.26
Combined Measured Resources	7.44	0.95	0.16	1.18	0.23	12	0.28
Combined Indicated Resources	15.5	0.92	0.09	1.06	0.46	14	0.53
Combined Inferred Resources	11.3	0.98	0.11	1.14	0.36	13	0.42
Combined Project Resources	34.3	0.95	0.11	1.11	1.04	38	1.23

Table 1: Combined MOGB Gold Project JORC (2012) resources.

- Notes:
1. The resources should be considered in-situ in accordance with JORC (2012) reporting guidelines.
 2. Cutoff grade of 0.5g/t AuEq was applied for Kopsa and 0.5g/t Au was applied for the Angesneva and Hirsikangas resource estimates, for the mineralisation deemed potentially mineable by open pit methods.
 3. AuEq figures for the Kopsa resource calculation and reporting used US\$1,500/oz gold price and US\$7,166/t copper price. A recovery factor of 80% was applied for both Au and Cu based on the 2013 Kopsa PEA metallurgical inputs. Resultant formula applied is $AuEq (g/t) = Au (g/t) + 1.49 * Cu (%)$. An updated AuEq formula has been applied when reporting of the Company's 2025 drill results based on updated commodity prices and a detailed review of the historical metallurgical results, but the formula applied for the Kopsa resource currently remains as originally calculated. The Company intends to update the Kopsa resource in 2026 to incorporate the latest drilling and metallurgical results with an updated AuEq formula. In the Company's opinion, the metals included in the Kopsa equivalent calculation (Au,Cu) have reasonable potential to be both recovered and sold.
 4. Discrepancies in the totals, products or percentages in the table are due to rounding effects.

⁹ Refer NNL ASX Announcements "Major Finland Gold Transaction", 11 April 2025 and "Kiimala Project Review adds further 147koz Gold in Indicated Resources", 29 May 2025 and "Hirsikangas Increases Gold Resources by 34% to over 1Moz", 14 July 2025.

Authorised for release by the Board of Directors.

For further information please contact:

Nordic Resources Ltd

Robert Wrixon – Managing Director

E: info@nordicresources.com

W: nordicresources.com

Competent Persons' Statements

The information in this announcement that relates to the Kopsa Exploration Results and the MOGB Mineral Resources is based on information compiled by Dr Hannu Makkonen, a consultant to the Company. Dr Makkonen is a European Geologist (EurGeol) as defined by the European Federation of Geologists.

The information in this announcement that relates to the Kopsa Metallurgical Results is based on information compiled by Mr Chris Martin, a consultant to the Company. Mr Martin has 40 years of experience in metallurgy and is a Member of the UK Institute of Materials, Minerals and Mining and a chartered engineer.

Both Dr Makkonen and Mr Martin have sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as Competent Persons as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves (JORC Code). Dr Makkonen and Mr Martin consent to the inclusion in this announcement of the matters based on their information in the form and context in which it appears.

Forward Looking Statements

This announcement contains forward-looking statements that involve a number of risks and uncertainties. These forward-looking statements are expressed in good faith and believed to have a reasonable basis. These statements reflect current expectations, intentions or strategies regarding the future and assumptions based on currently available information. Should one or more of the risks or uncertainties materialise, or should underlying assumptions prove incorrect, actual results may vary from the expectations, intentions and strategies described in this announcement. No obligation is assumed to update forward looking statements if these beliefs, opinions and estimates should change or to reflect other future developments.

Appendix 1

Kopsa Project - Drill Collar Locations and Composite Intersections

Hole ID	Easting ¹	Northing ¹	Elev. (m)	Azim. (°) ²	Dip (°) ³	Year ⁴	Depth (m)	Info	From (m)	To (m)	Interval (m) ⁵	Au (g/t)	Cu (%)	AuEq (g/t) ⁶	Ag (g/t)
NGKOP22013 (extended)	413004.0	7072832.1	110.4	23.0	47.0	2022	184.40		11.10	40.70	29.60	0.60	0.14	0.81	-
									55.40	74.40	19.00	0.53	0.09	0.66	-
						2026	262.00		211.90	216.60	4.70	0.82	0.17	1.00	4
NRKOP25005 (extended)	413047.7	7072736.3	111.3	21.7	45.5	2025	151.90		19.40	35.40	16.00	0.39	0.10	0.50	1
									57.20	87.20	30.00	0.67	0.15	0.83	2
									97.20	100.25	3.05	2.31	0.39	2.75	6
								incl.	99.05	100.25	1.20	5.42	0.30	5.75	5
						2026	386.00		176.60	178.60	2.00	0.36	0.15	0.52	<1
									204.60	206.60	2.00	1.61	0.08	1.69	2
									252.90	254.90	2.00	0.77	0.16	0.95	1
									260.90	262.90	2.00	0.47	0.13	0.62	1
									266.90	268.90	2.00	0.28	0.41	0.73	3
NRKOP26030	413458.5	7072803.4	108.0	30.0	44.8	2026	247.30		291.30	345.90	54.60	0.47	0.18	0.67	2
								incl.	340.00	344.50	4.50	2.50	0.19	2.70	5
									368.30	383.30	15.00	0.48	0.12	0.61	3
									5.70	12.10	6.40	0.65	0.12	0.79	1
									51.60	53.60	2.00	0.90	0.07	0.98	<1
									101.20	104.35	3.15	1.21	0.40	1.64	8
									112.40	114.40	2.00	0.43	0.08	0.52	1
									132.40	148.20	15.80	0.41	0.33	0.77	7
									162.20	164.20	2.00	0.66	0.03	0.69	1

¹ Coordinate system: ETRS-TM35FIN (EPSG: 3067).

² Azimuth is expressed in relation to the ETRS-TM35FIN grid north.

³ Dip is expressed in relation to 0° horizontal and +90° downward vertical.

⁴ Holes NGKOP22013 and NRKOP25005 were extended during the 2026 drilling program. Intersections from the 2022 drilling in the hole NGKOP22013 (highlighted in grey in the table) are shown as they were reported by Northgold using different selection criteria and gold equivalence calculations. For more information, see NNL ASX Announcements "Major Finland Gold Transaction" on 11 April 2025 for hole NGKOP22013 and "Substantial Further Extensions to Gold Mineralisation at Kopsa" on 8 December 2025 for hole NRKOP25005.

⁵ Metrics used for drill intersections: Grade cut-off of 0.5g/t AuEq and grade-thickness of 1.0g/t*m were applied as the lower cut-offs for reported intersections. The intervals are based on geologically selected intersections and may include variable amounts of allowed internal dilution below 0.3g/t AuEq.

⁶ The AuEq formula employs a US\$3,000/oz gold price and a US\$10,000/t copper price. A recovery factor of 80% is applied for Au and 85% for Cu based on the latest review of the 2012 Kopsa NI43-101 metallurgical studies and the 2013 Kopsa PEA by NNL's consultant Mr Chris Martin. Resultant formula applied is AuEq (g/t) = Au (g/t) + 1.102*Cu (%).

Appendix 2 JORC CODE, 2012 EDITION – TABLE 1 REPORT

Section 1 Sampling Techniques and Data (Criteria in this section apply to all succeeding sections)

Criteria	JORC Code explanation	Commentary
Sampling techniques	- Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. - Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. - Aspects of the determination of mineralisation that are Material to the Public Report. - In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.	- Samples and geological information were sourced using diamond drilling (DD). - Sampling and lithological intervals were determined by geologists with relevant experience. - DD core intervals selected for assaying were marked up and recorded for cutting and sampling. - Mineralisation and prospective lithologies are generally distinctive from the barren host lithologies. - All intersections are reported as downhole widths. - In total, 559.00m of new diamond drilling was completed by Nordic Resources Ltd (NNL) in one new and two extended DD holes. - All core was logged in detail and partially assayed by NNL.
Drilling techniques	Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Diamond drilling was 50.7mm NQ2 core, all of which was oriented using a Champ Ori device by Axis Mining Technology.
Drill sample recovery	- Method of recording and assessing core and chip sample recoveries and results assessed. - Measures taken to maximise sample recovery and ensure representative nature of the samples. - Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	- No core loss was noted. - There was no evidence of sample bias or any relationship between sample recovery and grade.
Logging	- Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. - Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. - The total length and percentage of the relevant intersections logged.	- Logging was completed by NNL geologists and geologists under NNL's supervision. - The logging is qualitative and quantitative. - Core photos were taken. 100% of core was logged from the relevant intersections.

Criteria	JORC Code explanation	Commentary
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i> <i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i> <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i> <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i> <i>Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second-half sampling.</i> <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	- The sampling of drill core was conducted as part of the logging procedure. - Full drill core samples were sent to the ALS Outokumpu facilities, where they were sawn longitudinally such that ½ core was taken for sample preparation. - Sample size in mineralised intervals varied between 0.95 – 3.10m, where the average sample size was 1.89m and total number of samples was 263. In addition, 6 samples from barren sections were assayed at wider intervals for waste rock characterisation. - It is considered that the sample sizes used are appropriate for the mineralisation at Kopsa.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i> <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i> <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i>	- Samples were sent from ALS Outokumpu to ALS Hub laboratory in Loughrea, Ireland, for PbO fire assay and ICP-AES or gravimetric analysis (method code: Au-ICP22 for <10 ppm Au and Au-GRA22 for >10 ppm Au samples); and for aqua regia acid digestion and ICP-AES analysis (method code: ME-ICP41a). - NNL has included periodic blank and standard samples in all of its assays to assess the performance of the used laboratory. In two standard samples out of 11, small deviations in Au grade (+0.016ppm absolute and +7.0% relative, in both) were noted. Otherwise, no QA/QC issues were noted with the reported results.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i> <i>The use of twinned holes.</i> <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> <i>Discuss any adjustment to assay data.</i>	Primary assay data is stored securely by NNL. Data entry to database is restricted, limited to selected personnel in the management.
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i> <i>Specification of the grid system used.</i> <i>Quality and adequacy of topographic control.</i>	- Locations and elevations have been DGPS-surveyed. The used coordinate system is ETRS-TM35FIN (EPSG:3067). An additional elevation dataset for confirmation has been determined from Finnish National Land Survey's LiDAR digital terrain model with a 2m lateral grid size and an estimated 30cm absolute and significantly higher relative accuracy for elevation. - Down-hole deviations surveyed using Devico DeviGyro instrument.
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i> <i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i> <i>Whether sample compositing has been applied.</i>	- Drilling is exploration drilling around the known resource. The distance from nearby drill holes of similar depth is approximately 60-120 meters, with many shallow historical drill holes collared closer, approximately at 30-40 meters distance. - The spacing of samples used is considered sufficient for the evaluation in this study.

Criteria	JORC Code explanation	Commentary
Orientation of data in relation to geological structure	- Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. - If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.	- The generalised deposit-scale envelope of the intrusive-hosted mineralisation is interpreted to dip approximately 20° towards south, whereas the smaller-scale structures (lodes, veins) have a near-vertical attitude and strike varying from E-W to NW-SE. - The holes have therefore been drilled in azimuths 22-30°, with dips ranging between 45° and 47°, in order to get as near perpendicular to the interpreted lode orientation as possible and collect meaningful structural data. - Intersections are quoted as down hole lengths; true thicknesses are estimated to be 70-80% of the down hole thickness. - Drilling orientations have not introduced any sampling bias that is considered material.
Sample security	The measures taken to ensure sample security.	NNL followed best practices to ensure sample security. The samples are stored in secure facilities and sample shipments were sent and received in supervision by NNL personnel.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	The QA/QC procedure and results are monitored by NNL personnel, and reviewed by Dr Hannu Makkonen, a consultant to the Company.

Section 2 Reporting of Exploration Results (Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	- Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. - The security of the tenure held at the time of reporting along with any known impediments to obtaining a license to operate in the area.	- The tenements are located in Haapajärvi, Finland, and held by Fennia Gold Oy, a 100% owned subsidiary of NNL. - All results in this announcement pertain to the tenement package consisting of the exploration licences (type of licence by Finnish Mining Law nomenclature and status in parentheses): Kopsankangas 7405/1 (Claim, valid), Kopsankangas 2 7686/1 (Claim, valid), Kopsa S ML2022:0062 (Exploration Permit, granted and under appeal), Kopsa SE ML2025:0059 (Exploration Permit, application), Kopsa SW VA2025:0045 (Reservation, valid), Korsuneva VA2026:0026 (Reservation, valid). - In addition to exploration licences, Fennia Gold Oy holds two mining licences in progress (type of licence by Finnish Mining Law nomenclature and status in parentheses): Kopsa K7405 (Mining Concession, conditionally approved), Kopsa KL2022:0005 (Aux Mining Permit, an auxiliary area to secure road access to the site, granted and under appeal). - Both the Aux Mining Permit and the Exploration Permit "Kopsa S" around the Kopsa Mining Concession and Claims have previously received approval from the Finnish Mining Authority, Tukes. The decisions are in an appeal process involving a consultation period and determination by the local administrative court. Additionally, two wind

Criteria	JORC Code explanation	Commentary
		power projects have plans overlapping with parts of the Exploration Permit area, but no zoning plans are currently approved. The licences are either valid or in the standard Finnish legal process and there are currently no known impediments to obtain the mining licence based on the current layout of the Mining Concession, nor to continue exploration within the current layouts of the two Claims.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	- Historical diamond drilling used in resource estimation was commissioned and managed by Glenmore Highlands / Baltic Minerals, Belvedere Resources / Belvedere Mining and Northgold. Earlier drilling was commissioned and managed by the Geological Survey of Finland and Outokumpu, but this data is not used in the MRE. - Northgold conducted 2D induced polarisation in 2022, and borehole and fixed loop electromagnetic surveys in 2022 and 2023.
Geology	Deposit type, geological setting and style of mineralisation.	- The main commodities of interest in the Kopsa projects are gold and copper, with potential silver credits. The main economic minerals of interest are native gold (fine-grained inclusions in arsenopyrite and chalcopyrite) and chalcopyrite. The bulk of the mineralisation occurs as disseminated and veinlets or stringers of sulphides with quartz veins, but there are also semi-massive sulphide veins. - The main mineralised lithologies are tonalite, quartz diorite, diorite and plagioclase porphyry inside an intrusive unit usually referred to as the "Kopsa tonalite". Also, some mineralisation is hosted by metasedimentary rocks surrounding the Kopsa tonalite. - The host intrusion and the surrounding metasedimentary and other units are part of the Middle Ostrobothnia Gold Belt (MOGB), a region hosting multiple gold and base metal deposits and occurrences. The MOGB is part of the Paleoproterozoic Svecofennian crustal domain.
Drill hole Information	- A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: - easting and northing of the drill hole collar - elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar - dip and azimuth of the hole - down hole length and interception depth - hole length. - If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	- Drill collar table with the newly reported significant intersections are presented in <i>Appendix 1</i>. All other drill holes that are referred to in figures and announcement are previously reported. - All drill holes are diamond cored.

Criteria	JORC Code explanation	Commentary
Data aggregation methods	<i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i> <i>Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i> <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i>	- Weighted average grade intersections are reported at a primary cut-off level of calculated gold equivalence (stated as "g/t AuEq"), where the intervals are based on geologically selected intersections and may include variable amounts of internal dilution. When calculating intersections, any missing values, including sections of core loss or assayed metal (Au, Cu, Ag) grades below their respective detection limits, are replaced with zero. - No top cuts have been applied to the reported grades. - Gold equivalence calculations for the newly reported intersections are based on a US\$3,000/oz gold price and US\$10,000/t copper price. Recovery factor of 80% is applied for Au and 85% for Cu based on the latest review of the 2012 Kopsa NI43-101 metallurgical studies and the 2013 Kopsa PEA by>NNL's consultant, Mr Chris Martin. Resultant formula applied is $AuEq (g/t) = Au (g/t) + 1.102 * Cu (\%)$.
Relationship between mineralisation widths and intercept lengths	<i>These relationships are particularly important in the reporting of Exploration Results.</i> <i>If the geometry of mineralisation with respect to the drill hole angle is known, its nature should be reported.</i> <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i>	The true thickness of mineralisation cannot be established with a high degree of certainty, but they are estimated to be 70-80% of the downhole thickness in drill core. Holes are inclined to get as near to perpendicular intersections as possible.
Diagrams	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i>	Relevant maps and sections are provided in the announcement: Plan views of Kopsa and the location of drill holes, and cross sections of Kopsa showing outlines of the latest MRE and host tonalite intrusion.
Balanced reporting	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	All available relevant information is reported.
Other substantive exploration data	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; deleterious or contaminating substances.</i>	None.
Further work	<i>The nature and scale of planned further work (eg tests for lateral or depth extensions or large-scale step-out drilling).</i> <i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i>	- Approx 14km of diamond drilling is planned to commence in Q3 2026 at the Company's MOGB projects. The drilling will focus on the geological understanding of, and continued resource growth at, Kopsa. - Borehole Electromagnetic (BHEM) surveys may be undertaken from time to time of certain deeper holes of particular interest.